

Backstand Centerless Cylindrical Rat Sander Air Drum

KK772X



VSM COMPACTGRAIN

Grain type A	luminum oxide granulate	Materia		
Bonding	Full-resin bonded	S	STAINLESS STEEL	
Color	Grey	Unalloved	Stainless Steel	
Backing	X-Polyester	Steel		
Flexibility	Sturdy	Feature	es	
Production widt	h 44 in	\odot		\bigcirc
		Medium	Medium	Also for we

Long-term compactgrain abrasive with continuous self-sharpening effect that reduces grinding costs due to fewer tool changes and is characterized by constant, high stock removal with even surface roughness over its entire, very long service life.

Grit range:1)

ant	lang	e. 1)																						
								Ρ		Р		Р		Ρ		Ρ		Ρ		Ρ	Ρ			
16	20	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	

Benefits

- > Consistent stock removal
- > Uniform scratch pattern and consistent surface roughness
- > Very long service life

Wear pattern of the grain



t=0

MADE IN GERMANY

Grinding time

VSM COMPACTGRAIN series are completely made of granules which consist of numerous abrasive grains. The used grains are torn out by the cutting forces involved whereby unused grain tips are being exposed.

GFEP

VSM Abrasives Corp.

1012 East Wabash Street · O'Fallon, MO 63366 · USA T +1 800 737 0176 · F +1 636 272 6394 us.info@vsmabrasives.com · www.us.vsmabrasives.com

¹⁰ P = Categorized according to the FEPA standard. Further grit sizes upon request. Subject to technical changes.